

XTR-3924FX22-DN / X26-DN

Speed Dome Color Camera



XTRACK
new concept in CCTV systems



- 4.9-inch acrylic bubble
- Up to 240 programmable preset positions
- Optional Manual/Auto Night shot and slow shutter function enhances
- Diagonal Scanning (Vector Scanning)
- Optional Indoor/Outdoor pendant mount, flush mount, parapet mount and roof top mount
- Auto focus/Iris with Manual Override
- AC Line Lock (Remote Control)
- Quick Detachable (Hot Swap)
- Offset (Recalibration) of Preset Angle
- Data Up/Down load (Preset, Tour, Etc...)
- 8 Privacy Zone
- Easy DVR and multiplexer remote control
- 5-inch Color LCD keyboard

Specifications

MODEL	XTR-3424FX26-DN	XTR-3424FX22-DN
MODULE		
CCD Type	1/4" Type Ex-view CCD	1/4" Type Super HAD CCD
Optical / Digital Zoom	26× / 12×	22× / 11×
Resolution (NTSC / PAL)	470 / 460 TVL	470/460TVL
Focal length	3.5 mm ~ 91 mm	3.9 mm ~ 85.8 mm
Min. Illumination		
• Normal (50IRE)	1.0 Lux	0.5 Lux
• Low Shutter (1/4(3))	0.07 Lux	0.02 Lux
• ICR on & Low Shutter	0.01 Lux	0.01 Lux
Image Stabilizer	NO	NO
WDR	NO	NO
ICR on	YES	YES
Angle of View	3.5 mm : 54.2° 91 mm : 2.2°	3.9 mm : 49° 85.8 mm : 2.4°
DOME		
Panning angle (Optional)	360° continuous rotation	
Alarm (Optional)	8 inputs (NC/NO), 4 relay outputs	
Tilt angle	-10 ~ 90	
Auto Scan	1 auto pan & 8 auto scan capability	
Preset	240 presets with individual dwell time	
Pattern	4 patterns (recording up to 240 sec.)	
Tour	8 tours (consist of 32 functions/1 tour)	
Max Speed	380 / sec	
Area Title	it can be divided 16 areas with 16 characters of title	
Privacy Zone	8 privacy zone masking (2 methods selectable : mark / video off)	

Specifications subject to change without notice


Housing



XTR-969E-SH outdoor



XTR-969I indoor



Housing	
power source	24VAC, 50/60 Hz
heater	50W
blower	6W
construction	ALUMINIUM, STEEL & PLASTIC
weight	4.3 KG
etc	OPTIONAL SMOKE BUBBLE

Optional Products

